

ASKING FOR ASSISTANCE

Technical Support:

Telephone (818) 884-6294
(800) 545-6900

Fax (818) 884-3108

Technical Support Hours:

8:00 AM to 5:00 PM Monday thru Friday PST.

Write To:

Gefen Inc.
c/o Customer Service
20600 Nordhoff Street
Chatsworth CA 91311 USA

support@gefen.com -- www.gefen.com

Notice

Gefen Inc. reserves the right to make changes in the hardware, packaging and any accompanying documentation without prior written notice.

HDMI Digital Audio Splitter is a trademark of Gefen Inc.

TABLE OF CONTENTS

- 1 Introduction
- 2 Features
- 3 Panel Descriptions
- 4 Connecting and Operating the HDMI Digital Audio Splitter
- 5 RMT4-IR Installation
- 6 Specifications
- 7 Warranty

INTRODUCTION

Congratulations on your purchase of the ex•tend•it HDMI Digital Audio Splitter. Your complete satisfaction is very important to us.

Gefen's line of HDTV switches, extenders, and splitters are designed to make your A/V equipment use more comfortable, more productive and less expensive.

Gefen's ex•tend•it HDMI Digital Audio Splitter is a distribution hub that sends the same video output to two or more HDTV digital screens. It is a flexible solution that accommodates multiple displays. When two or more HDMI splitters are connected together, they can be used to create a larger distribution.

The HDMI Digital Audio Splitter is connected using a HDMI cable from the HDMI source to the HDMI splitter input. There are two HDMI outputs. HDMI output 1 is the primary connection and is used for the main display. HDMI output 2 follows the main display.

The HDMI splitter is HDCP compliant.

The ex•tend•it line offers solutions for noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

Our Commitment

Gefen will always offer the finest quality product at the best possible price. Included in that price is a lifetime of support from a team of outstanding engineers.

FEATURES

Features

- Splits the HDTV HDMI signal to two or more HDTV displays
- Maintains 480i, 480p, 720p, 720i, and 1080i, 1080p resolutions
- Connects two or more HDTV displays at the same time to the same video source
- Uses HDMI cables to connect to the input and splitter output
- Maintains highest DVI single link video resolution
- Supports DDWG standard for DVI compliant monitors
- Supports HDCP compliant devices
- Supports DDWG standard for HDMI compliant monitors
- Installs in seconds

Includes:

6' HDMI cable (m-m)
6' Toslink cable
5VDC Power Supply
The HDMI Digital Audio Splitter

PANEL DESCRIPTIONS



SPDIF In Optical In HDMI In 5v Power Input



SPDIF Out Optical Out HDMI Out HDMI Out SPDIF Out Optical Out

Connecting and Operating the HDMI Digital Audio Splitter

How to Connect the HDMI Digital Audio Splitter to your devices

- 1- Connect the supplied HDMI cable from the HDMI device into the HDMI Splitter Input.
- 2- Connect the cable from your first display (monitor or projector) into the HDMI Out 1 slot in the back of the HDMI Splitter
- 3- Connect the cable from your second display (monitor or projector) into the HDMI Out 2 slot in the back of the HDMI Splitter.
- 4- Plug the 5v power supply into the HDMI Splitter.
- 5- Plug the 5v wallmount power supply into the wall outlet.

NOTE: The HDMI Splitter only passes digital video, and does not support digital audio in HDMI.

Connecting either a SPDIF or Toslink into the Digital Audio input will convert and distribute to both the SPDIF and Toslink outputs on each distribution.

SPECIFICATIONS

Video Amplifier Bandwidth	1.65 GHz
Input Video Signal	1.2 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Maximum Single Link Range	1920 x 1200, 1080p
DVI Input/Output Connector Type	DVI-D
Power Consumption	15 Watts (max.)
Power Supply	5VDC
Dimensions	6"W x 1"H x 4.7"D
Shipping Weight	2 Lbs

WARRANTY

Gefen Inc. warrants the equipment it manufactures to be free from defects in material and workmanship.

If equipment fails because of such defects and Gefen Inc. is notified within one (1) year from the date of shipment, Gefen Inc. will, at its option, repair or replace the equipment, provided that the equipment has not been subjected to mechanical, electrical, or other abuse or modifications.

Equipment that fails under conditions other than those covered will be repaired at the current price of parts and labor in effect at the of repair. Such repairs are warranted for ninety (90) days from the day of reshipment to the Buyer.

This warranty is in lieu of all other warranties expressed or implied, including without limitation, any implied warranty or merchantability or fitness for any particular purpose, all of which are expressly disclaimed.

The information in this manual has been carefully checked and is believed to be accurate. However, Gefen Inc. assumes no responsibility for any inaccuracies that may be contained in this manual. In no event will Gefen Inc., be liable for direct, indirect, special, incidental, or consequential damages resulting from any defect or omission in this manual, even if advised of the possibility of such damages. The technical information contained herein regarding HDMI Digital Audio Splitter features and specifications is subject to change without notice.